

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs	Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	---	---	--	---	---	3,80	9,0	14,5	18,0	1,20	15,0
0,40	---	---	--	---	---	4,00	25,0	34,0	50,0	1,07	47,0
0,60	---	---	--	0,07	---	4,20	42,0	50,0	84,0	1,33	63,0
0,80	6,5	7,0	13,0	0,40	32,0	4,40	42,0	52,0	84,0	1,60	52,0
1,00	3,0	6,0	6,0	0,13	45,0	4,60	32,0	44,0	64,0	1,67	38,0
1,20	4,5	5,5	9,0	0,47	19,0	4,80	25,5	38,0	51,0	1,53	33,0
1,40	5,0	8,5	10,0	0,33	30,0	5,00	14,5	26,0	29,0	1,13	26,0
1,60	6,5	9,0	13,0	0,73	18,0	5,20	14,5	23,0	29,0	0,67	43,0
1,80	6,0	11,5	12,0	0,60	20,0	5,40	13,0	18,0	26,0	0,47	56,0
2,00	7,0	11,5	14,0	1,00	14,0	5,60	23,5	27,0	47,0	0,93	50,0
2,20	8,0	15,5	16,0	1,07	15,0	5,80	14,0	21,0	28,0	1,00	28,0
2,40	7,0	15,0	14,0	0,93	15,0	6,00	10,5	18,0	21,0	0,67	31,0
2,60	9,0	16,0	18,0	1,00	18,0	6,20	13,0	18,0	26,0	0,87	30,0
2,80	9,5	17,0	19,0	1,20	16,0	6,40	19,0	25,5	38,0	1,07	36,0
3,00	8,0	17,0	16,0	0,87	18,0	6,60	20,0	28,0	40,0	1,13	35,0
3,20	8,0	14,5	16,0	0,87	18,0	6,80	14,0	22,5	28,0	1,07	26,0
3,40	7,5	14,0	15,0	0,67	22,0	7,00	15,0	23,0	30,0	---	---
3,60	8,0	13,0	16,0	0,73	22,0						

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
- punta meccanica tipo Begemann ø = 35.7 mm (area punta 10 cm² - apertura 60°)
- manicotto laterale (superficie 150 cm²)