

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	---	---	---	---	---
0,40	---	---	---	0,40	---
0,60	5,5	8,5	11,0	0,73	15,0
0,80	6,5	12,0	13,0	0,47	28,0
1,00	3,5	7,0	7,0	0,33	21,0
1,20	4,5	7,0	9,0	0,27	34,0
1,40	9,0	11,0	18,0	0,60	30,0
1,60	5,5	10,0	11,0	0,67	16,0
1,80	4,5	9,5	9,0	0,53	17,0
2,00	4,5	8,5	9,0	0,53	17,0
2,20	5,5	9,5	11,0	2,53	4,0
2,40	25,0	44,0	50,0	1,60	31,0
2,60	40,0	52,0	80,0	1,27	63,0
2,80	6,0	15,5	12,0	0,60	20,0
3,00	7,5	12,0	15,0	0,80	19,0
3,20	8,5	14,5	17,0	0,53	32,0
3,40	9,5	13,5	19,0	0,67	28,0
3,60	11,0	16,0	22,0	0,80	27,0
3,80	10,0	16,0	20,0	1,13	18,0
4,00	8,5	17,0	17,0	1,27	13,0

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
4,20	7,0	16,5	14,0	1,00	14,0
4,40	6,5	14,0	13,0	0,87	15,0
4,60	6,5	13,0	13,0	0,73	18,0
4,80	3,5	9,0	7,0	0,27	26,0
5,00	3,0	5,0	6,0	0,40	15,0
5,20	4,0	7,0	8,0	0,33	24,0
5,40	7,0	9,5	14,0	0,80	17,0
5,60	7,0	13,0	14,0	0,73	19,0
5,80	9,5	15,0	19,0	0,93	20,0
6,00	11,0	18,0	22,0	1,47	15,0
6,20	10,0	21,0	20,0	1,20	17,0
6,40	7,5	16,5	15,0	0,80	19,0
6,60	8,5	14,5	17,0	0,80	21,0
6,80	6,5	12,5	13,0	0,60	22,0
7,00	2,0	6,5	4,0	0,40	10,0
7,20	7,0	10,0	14,0	0,60	23,0
7,40	8,0	12,5	16,0	0,80	20,0
7,60	6,5	12,5	13,0	0,80	16,0
7,80	7,0	13,0	14,0	1,07	13,0
8,00	7,5	15,5	15,0	---	---

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
- punta meccanica tipo Begemann ø = 35.7 mm (area punta 10 cm² - apertura 60°)
- manicotto laterale (superficie 150 cm²)