

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
------------	-----------------------------	-----------------------------	--------------------------	--------------------------	-------

0,20	—	—	—	—	—
0,40	—	—	—	0,20	—
0,60	2,5	4,0	5,0	0,27	19,0
0,80	2,5	4,5	5,0	0,67	7,0

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
------------	-----------------------------	-----------------------------	--------------------------	--------------------------	-------

1,00	4,0	9,0	8,0	0,53	15,0
1,20	11,0	15,0	22,0	1,47	15,0
1,40	12,0	23,0	24,0	1,80	13,0
1,60	11,0	24,5	22,0	—	—

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
- punta meccanica tipo Begemann $\phi = 35.7$ mm (area punta 10 cm² - apertura 60°)
- manicotto laterale (superficie 150 cm²)



