

Prof.(m)	N(colpi p)	Rpd(kg/cm ²)	N(colpi r)	asta	Prof.(m)	N(colpi p)	Rpd(kg/cm ²)	N(colpi r)	asta
0.00 - 0.10	4	18.8	---	1	1.70 - 1.80	25	110.3	---	2
0.10 - 0.20	5	23.4	---	1	1.80 - 1.90	26	108.3	---	3
0.20 - 0.30	5	23.4	---	1	1.90 - 2.00	38	158.3	---	3
0.30 - 0.40	7	32.8	---	1	2.00 - 2.10	21	87.5	---	3
0.40 - 0.50	4	18.8	---	1	2.10 - 2.20	26	108.3	---	3
0.50 - 0.60	6	28.1	---	1	2.20 - 2.30	42	175.0	---	3
0.60 - 0.70	3	14.1	---	1	2.30 - 2.40	31	129.2	---	3
0.70 - 0.80	2	9.4	---	1	2.40 - 2.50	38	158.3	---	3
0.80 - 0.90	2	8.8	---	2	2.50 - 2.60	61	254.2	---	3
0.90 - 1.00	1	4.4	---	2	2.60 - 2.70	24	100.0	---	3
1.00 - 1.10	1	4.4	---	2	2.70 - 2.80	31	129.2	---	3
1.10 - 1.20	2	8.8	---	2	2.80 - 2.90	22	86.8	---	4
1.20 - 1.30	4	17.6	---	2	2.90 - 3.00	16	63.2	---	4
1.30 - 1.40	5	22.1	---	2	3.00 - 3.10	23	90.8	---	4
1.40 - 1.50	12	52.9	---	2	3.10 - 3.20	38	150.0	---	4
1.50 - 1.60	19	83.8	---	2	3.20 - 3.30	45	177.6	---	4
1.60 - 1.70	21	92.6	---	2	3.30 - 3.40	110	434.2	---	4

- PENETROMETRO DINAMICO tipo : DL030 - SUNDA

- M (massa battente)= 30.00 kg - H (altezza caduta)= 0.20 m - A (area punta)= 10.00 cm² - D(diam. punta)= 35.70 mm

- Numero Colpi Punta N = N(10) [δ = 10 cm]

- Uso rivestimento / fanghi iniezione : SI