

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs	Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	---	---	---	---	---	2,80	6,0	11,5	12,0	0,67	18,0
0,40	---	---	---	0,40	---	3,00	5,5	10,5	11,0	0,27	41,0
0,60	2,5	5,5	5,0	0,20	25,0	3,20	14,0	16,0	28,0	0,33	84,0
0,80	5,5	7,0	11,0	0,20	55,0	3,40	13,0	15,5	26,0	0,40	65,0
1,00	2,5	4,0	5,0	0,20	25,0	3,60	17,0	20,0	34,0	0,67	51,0
1,20	3,5	5,0	7,0	0,13	52,0	3,80	13,5	18,5	27,0	0,33	81,0
1,40	3,5	4,5	7,0	0,20	35,0	4,00	20,0	22,5	40,0	0,40	100,0
1,60	3,5	5,0	7,0	0,07	105,0	4,20	22,0	25,0	44,0	0,67	66,0
1,80	4,0	4,5	8,0	0,20	40,0	4,40	21,5	26,5	43,0	0,80	54,0
2,00	3,0	4,5	6,0	0,27	22,0	4,60	26,0	32,0	52,0	0,53	97,0
2,20	4,0	6,0	8,0	0,07	120,0	4,80	24,5	28,5	49,0	0,60	82,0
2,40	6,5	7,0	13,0	0,67	19,0	5,00	27,0	31,5	54,0	0,80	67,0
2,60	5,0	10,0	10,0	0,73	14,0	5,20	54,0	60,0	108,0	---	---

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
 - COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
 - punta meccanica tipo Begemann $\varnothing = 35.7$ mm (area punta 10 cm² - apertura 60°)
 - manicotto laterale (superficie 150 cm²)