

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs	Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	---	---	--	---	---	4,20	11,0	22,5	22,0	1,40	16,0
0,40	---	---	--	0,73	---	4,40	7,5	18,0	15,0	1,13	13,0
0,60	11,5	17,0	23,0	2,07	11,0	4,60	9,0	17,5	18,0	1,40	13,0
0,80	10,5	26,0	21,0	2,40	9,0	4,80	13,0	23,5	26,0	1,93	13,0
1,00	10,0	28,0	20,0	1,93	10,0	5,00	15,0	29,5	30,0	2,00	15,0
1,20	9,0	23,5	18,0	1,93	9,0	5,20	15,0	30,0	30,0	1,80	17,0
1,40	8,5	23,0	17,0	1,87	9,0	5,40	15,5	29,0	31,0	2,07	15,0
1,60	7,0	21,0	14,0	1,47	10,0	5,60	14,0	29,5	28,0	2,00	14,0
1,80	10,5	21,5	21,0	1,60	13,0	5,80	15,0	30,0	30,0	1,73	17,0
2,00	9,0	21,0	18,0	1,47	12,0	6,00	13,0	26,0	26,0	2,13	12,0
2,20	10,5	21,5	21,0	1,07	20,0	6,20	15,0	31,0	30,0	2,20	14,0
2,40	10,0	18,0	20,0	1,27	16,0	6,40	14,0	30,5	28,0	2,20	13,0
2,60	9,0	18,5	18,0	1,20	15,0	6,60	14,0	30,5	28,0	2,13	13,0
2,80	9,0	18,0	18,0	1,20	15,0	6,80	5,0	21,0	10,0	1,13	9,0
3,00	9,5	18,5	19,0	1,20	16,0	7,00	9,0	17,5	18,0	1,00	18,0
3,20	5,0	14,0	10,0	1,13	9,0	7,20	7,5	15,0	15,0	0,47	32,0
3,40	10,0	18,5	20,0	0,87	23,0	7,40	5,5	9,0	11,0	0,53	21,0
3,60	9,0	15,5	18,0	1,07	17,0	7,60	4,0	8,0	8,0	0,73	11,0
3,80	9,0	17,0	18,0	1,00	18,0	7,80	6,0	11,5	12,0	0,60	20,0
4,00	11,0	18,5	22,0	1,53	14,0	8,00	6,0	10,5	12,0	---	---

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
 - COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
 - punta meccanica tipo Begemann $\phi = 35.7$ mm (area punta 10 cm² - apertura 60°)
 - manicotto laterale (superficie 150 cm²)