

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	----	----	--	-----	----
0,40	----	----	--	-----	----
0,60	----	----	--	0,27	----
0,80	4,0	6,0	8,0	0,27	30,0
1,00	6,0	8,0	12,0	0,60	20,0
1,20	4,5	9,0	9,0	0,20	45,0
1,40	8,0	9,5	16,0	0,67	24,0
1,60	8,5	13,5	17,0	0,47	36,0
1,80	8,5	12,0	17,0	0,40	42,0
2,00	9,5	12,5	19,0	0,93	20,0
2,20	8,0	15,0	16,0	0,80	20,0
2,40	8,5	14,5	17,0	0,73	23,0
2,60	9,5	15,0	19,0	1,00	19,0
2,80	9,0	16,5	18,0	1,20	15,0
3,00	9,0	18,0	18,0	1,00	18,0
3,20	9,5	17,0	19,0	1,07	18,0
3,40	9,5	17,5	19,0	1,07	18,0
3,60	10,0	18,0	20,0	0,87	23,0

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
3,80	8,5	15,0	17,0	1,00	17,0
4,00	9,0	16,5	18,0	1,07	17,0
4,20	10,5	18,5	21,0	1,33	16,0
4,40	22,0	32,0	44,0	1,73	25,0
4,60	35,0	48,0	70,0	1,33	52,0
4,80	40,0	50,0	80,0	1,87	43,0
5,00	38,0	52,0	76,0	1,20	63,0
5,20	27,0	36,0	54,0	1,20	45,0
5,40	15,0	24,0	30,0	0,67	45,0
5,60	13,0	18,0	26,0	0,87	30,0
5,80	14,0	20,5	28,0	1,00	28,0
6,00	10,0	17,5	20,0	0,67	30,0
6,20	12,0	17,0	24,0	0,80	30,0
6,40	18,0	24,0	36,0	0,93	39,0
6,60	15,0	22,0	30,0	1,00	30,0
6,80	14,0	21,5	28,0	1,20	23,0
7,00	15,0	24,0	30,0	-----	----

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
- punta meccanica tipo Begemann $\phi = 35.7$ mm (area punta 10 cm² - apertura 60°)
- manicotto laterale (superficie 150 cm²)