

Prof. m	RP/10 kg/cm <sup>2</sup>	RL/10 kg/cm <sup>2</sup>	Qc kg/cm <sup>2</sup>	fs kg/cm <sup>2</sup>	Qc/fs	Prof. m	RP/10 kg/cm <sup>2</sup>	RL/10 kg/cm <sup>2</sup>	Qc kg/cm <sup>2</sup>	fs kg/cm <sup>2</sup>	Qc/fs
0,20	—	—	—	—	—	3,80	6,5	13,0	13,0	0,67	19,0
0,40	—	—	—	0,47	—	4,00	5,0	10,0	10,0	1,13	9,0
0,60	3,0	6,5	6,0	0,13	45,0	4,20	6,5	15,0	13,0	1,20	11,0
0,80	4,0	5,0	8,0	0,33	24,0	4,40	14,0	23,0	28,0	1,60	17,0
1,00	2,5	5,0	5,0	0,27	19,0	4,60	15,0	27,0	30,0	1,33	22,0
1,20	3,0	5,0	6,0	0,20	30,0	4,80	15,0	25,0	30,0	1,47	20,0
1,40	3,0	4,5	6,0	0,27	22,0	5,00	15,0	26,0	30,0	1,60	19,0
1,60	4,5	6,5	9,0	0,40	22,0	5,20	16,0	28,0	32,0	1,20	27,0
1,80	4,0	7,0	8,0	0,40	20,0	5,40	19,0	28,0	38,0	1,60	24,0
2,00	4,0	7,0	8,0	0,47	17,0	5,60	20,0	32,0	40,0	1,33	30,0
2,20	5,0	8,5	10,0	0,33	30,0	5,80	17,0	27,0	34,0	1,33	25,0
2,40	2,5	5,0	5,0	0,20	25,0	6,00	15,0	25,0	30,0	1,33	22,0
2,60	3,0	4,5	6,0	0,27	22,0	6,20	10,0	20,0	20,0	1,73	12,0
2,80	3,0	5,0	6,0	0,07	90,0	6,40	20,0	33,0	40,0	1,47	27,0
3,00	6,0	6,5	12,0	0,53	22,0	6,60	18,0	29,0	36,0	1,73	21,0
3,20	8,0	12,0	16,0	0,80	20,0	6,80	17,0	30,0	34,0	2,27	15,0
3,40	9,0	15,0	18,0	0,80	22,0	7,00	17,0	34,0	34,0	2,13	16,0
3,60	8,0	14,0	16,0	0,87	18,0	7,20	19,0	35,0	38,0	—	—

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -  
 - COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s  
 - punta meccanica tipo Begemann  $\phi = 35.7$  mm (area punta 10 cm<sup>2</sup> - apertura 60°)  
 - manicotto laterale (superficie 150 cm<sup>2</sup>)



