

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
0,20	2,0	3,0	4,0	0,27	15,0
0,40	7,0	9,0	14,0	0,20	70,0
0,60	13,0	14,5	26,0	1,47	18,0
0,80	9,0	20,0	18,0	1,13	16,0
1,00	6,0	14,5	12,0	0,53	22,0
1,20	3,5	7,5	7,0	0,20	35,0
1,40	4,0	5,5	8,0	0,13	60,0
1,60	3,5	4,5	7,0	0,07	105,0
1,80	3,5	4,0	7,0	0,20	35,0
2,00	4,0	5,5	8,0	0,40	20,0
2,20	4,5	7,5	9,0	0,53	17,0

Prof. m	RP/10 kg/cm ²	RL/10 kg/cm ²	Qc kg/cm ²	fs kg/cm ²	Qc/fs
2,40	4,5	8,5	9,0	0,53	17,0
2,60	1,5	5,5	3,0	0,53	6,0
2,80	4,0	8,0	8,0	0,60	13,0
3,00	4,0	8,5	8,0	0,40	20,0
3,20	5,0	8,0	10,0	0,53	19,0
3,40	11,0	15,0	22,0	3,47	6,0
3,60	20,0	46,0	40,0	4,40	9,0
3,80	25,0	58,0	50,0	3,73	13,0
4,00	50,0	78,0	100,0	6,40	16,0
4,20	30,0	78,0	60,0	4,00	15,0
4,40	90,0	120,0	180,0	-----	----

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s
- punta meccanica tipo Begemann ø = 35.7 mm (area punta 10 cm² - apertura 60°)
- manicotto laterale (superficie 150 cm²)