

Prof. m	RP/10 kg/cm <sup>2</sup>	RL/10 kg/cm <sup>2</sup>	Qc kg/cm <sup>2</sup>	fs kg/cm <sup>2</sup>	Qc/fs	Prof. m	RP/10 kg/cm <sup>2</sup>	RL/10 kg/cm <sup>2</sup>	Qc kg/cm <sup>2</sup>	fs kg/cm <sup>2</sup>	Qc/fs
0,20	—	—	—	—	—	2,00	14,0	18,0	28,0	0,33	84,0
0,40	—	—	—	0,20	—	2,20	20,0	22,5	40,0	0,60	67,0
0,60	2,5	4,0	5,0	0,20	25,0	2,40	23,0	27,5	46,0	0,53	86,0
0,80	4,5	6,0	9,0	0,40	22,0	2,60	24,0	28,0	48,0	0,27	180,0
1,00	6,0	9,0	12,0	0,13	90,0	2,80	29,0	31,0	58,0	0,33	174,0
1,20	14,0	15,0	28,0	0,53	52,0	3,00	28,0	30,5	56,0	0,53	105,0
1,40	17,0	21,0	34,0	0,53	64,0	3,20	26,0	30,0	52,0	1,33	39,0
1,60	10,0	14,0	20,0	0,73	27,0	3,40	30,0	40,0	60,0	1,33	45,0
1,80	8,0	13,5	16,0	0,53	30,0	3,60	85,0	95,0	170,0	—	—

- PENETROMETRO STATICO tipo GOUDA da 5 t - (con anello allargatore) -  
- COSTANTE DI TRASFORMAZIONE Ct = 20 - Velocità Avanzamento punta 2 cm/s  
- punta meccanica tipo Begemann ø = 35.7 mm (area punta 10 cm<sup>2</sup> - apertura 60°)  
- manicotto laterale (superficie 150 cm<sup>2</sup>)